

SMS-LED

LED SEALED SURFACE MOUNT TROFFER



FEATURES

- L80 B10.
- Rated 70,000 hours.
- CRI>80.
- Self cooling, zhaga certified LED boards.
- 10 Year Warranty (Standard TCI).
- Heavy duty neoprene gasket ensures dust, insect and splash proof sealed for kitchens, hospitals, clean rooms and food preparation areas.
- 0.7mm Powder coated white metal body - other colours available upon request.
- Inverted diffuser in a screw fixed frame.
- Diffuser frame is connected to the body by safety lanyards.
- Suitable for fixing directly to ceiling or suspended with rods.
- Suitable for in-line mounting.
- Available in DALI dim or switch dim.
- High CRI available upon request.
- Clinical observation available upon request.



10
Year
Warranty



80
CRI typically
greater than



TECHNICAL INFORMATION

Contact Frend for other lighting configurations

Configurations	Non Dim System wattage	Combined Board Output (lm)	Nominal Dimensions (mm)
1x08W	10.60	1220	600x300
2x08W	22.20	2440	600x300 & 1200x300
3x08W	28.76	3660	600x600
4x08W	38.10	4880	1200x300 & 1200x600
1x14W	17.62	2200	600x300
2x14W	34.34	4400	600x300 & 1200x300
3x14W	51.92	6600	600x600
4x14W	68.52	8800	1200x300 & 1200x600

SPECIFICATIONS

Dimensions (mm)	
	Actual / Nominal
Length	612 / 600 1222 / 1200
Width	300 / 300 602 / 600
Depth	100

PRODUCT CODE

Example code: SMS-LED/4x08/12x3/LO/40/ND

See Technical Information Table for configurations options.
Specifications subject to change without notice.

Product Series	Number of Boards	Wattage of Boards	Nominal Dimensions	Diffuser	LED Type	ECG
SMS-LED Surface Mount	1	08	6x3 600x300	LO White Acrylic	30 3000K	ND Non Dimming
	2	14	6x6 600x600	MP Microprism	40 4000K	DALI DALI Dimming
	3		12x3 1200x300			SD Switch Dim
	4		12x6 1200x600			

FREND
lighting

phone 1300 241 087

fax (617) 3272 9000

email sales@foslighting.com.au

PO Box 268

14 Jaybel Street, Salisbury

Brisbane QLD 4107

www.frend.com.au