

ROB-LED

LED SLIMLINE OVERBED LIGHT



FEATURES

- L80 B10.
- 10 year warranty (standard TCI).
- Rated at 70,000 hrs.
- Architectural Slim line Design.
- Wall mounted luminaire designed to meet lighting requirements for hospitals, nursing homes and aged care facilities.
- Future proof replacement gear tray.
- Separately switched upward lighting and downward lighting.
- Upward light will provide general room lighting while downward lighting will provide specific task lighting eg. Reading light.
- White Acrylic Diffuser.
- Standard Fitting Powder coated white, other colours available upon request.
- Lumieo Diffuser.
- Quick disconnect.
- 8W LED boards - 1220 Lumens Output.
- 14W LED boards - 2200 Lumens Output.

TECHNICAL INFORMATION

Contact Frend for other lighting configurations
Refer to IES files for System Lumens

Configurations	Non Dim System wattage	Combined Board Output (lm)	Nominal Dimensions (mm)
1x08W	10.6	1220	600
2x08W	22.20	2440	1200
1x14W	17.62	2200	600
2x14W	34.34	4400	1200

SPECIFICATIONS

Dimensions (mm)	
	Actual / Nominal
Length	660 / 600
Width	152
Depth	61

PRODUCT CODE

Example code: ROB-LED/2X14U/2X08D/LO/40/ND

See Technical Information Table for configurations options
Specifications subject to change without notice

Product Series	Number of Boards	Upward Light	Downward Light	Diffuser	LED Type	ECG
ROB-LED	1	1x08U	1x08D	LO White Acrylic	30 3000K	ND Non Dim
	2	2x08U	2x08D		40 4000K	DALI DALI Dim
		1x14U	1x14D			SD Switch Dim
		2x14U	2x14D			SEP/SW Separately Switched

FREND
lighting

phone 1300 241 087

fax (617) 3272 9000

email sales@foslighing.com.au

PO Box 268

14 Jaybel Street, Salisbury

Brisbane QLD 4107

www.frend.com.au