

RLP

LED TROFFER



FEATURES

- L80 B10.
- Rated 70,000 hours.
- CRI>80.
- SELV.
- Self cooling, Zhaga certified LED boards.
- 10 year warranty.
- Remote gear.
- Available in plaster recessed and T-Bar recessed (38mm standard T-Bar).
- Available in DALI dim or switch dim.
- High CRI available upon request.
- Clinical observation available upon request.

SPECIFICATIONS

T-bar - Dimensions (mm)	
	Actual / Nominal
Length	595 / 600 1195 / 1200
Width	295 / 300 595 / 600
Depth	77
Plaster - Dimensions (mm)	
Length	634 / 600 1234 / 1200
Width	332 / 300 632 / 600
Depth	79
Plaster cut-out - Dimensions (mm)	
1198x298	1200x300
598x298	600x300
598x598	600x600

TECHNICAL INFORMATION

Contact Frend for other lighting configurations

Configurations	Non Dim System wattage	Combined Board Output (lm)	Nominal Dimensions (mm)
1x08W	10.6	1220	600x300
2x08W	22.2	2440	600x300 & 1200x300
3x08W	28.76	3660	600x600
4x08W	38.1	4880	1200x300 & 600x600
1x14W	17.62	2200	600x300
2x14W	34.34	4400	600x300 & 1200x300
3x14W	51.92	6600	600x600
4x14W	68.52	8800	1200x300 & 600x600

PRODUCT CODE

Example code: RLP-TB/4X14/12X3/LO/40/ND

See Technical Information Table for configurations options
Specifications subject to change without notice

Product Series		Number of Boards	Wattage of Boards	Nominal Dimensions	Diffuser type	LED Type	ECG
RLP-TB	T-Bar	1	08	6X3 600x300	LO White Acrylic	30 3000K	ND Non Dim
RLP-PB	Plaster	2	14	6X6 600x600	MP Microprism	40 4000K	DALI DALI Dim
		3		12X3 1200x300			SD Switch Dim
		4					

FREND
lighting

phone 1300 241 087

fax (617) 3272 9000

email sales@foslighting.com.au

PO Box 268

14 Jaybel Street, Salisbury

Brisbane QLD 4107

www.frend.com.au