

REVO

LOW PROFILE LED TROFFER



FEATURES

- L90 Rated at 60,000 hours.
- Rated 60,000 hours.
- CRI>80.
- 5 year warranty.
- Supplied with a Remote Driver to suit.
- Low Profile LED Luminaire with White Acrylic Lens (standard version).
- White powder coat finish.
- Air Handling version available at >400mm wide (REVO-AH).
- Available in T-Bar recessed or Plaster Recessed.
- Available in DALI Dim or Switch Dim.
- High CRI available upon request.
- Clinical Observation available upon request.



Year
Warranty



CRI typically
greater than

TECHNICAL INFORMATION

Contact Frend for other lighting configurations
Refer to IES files for System Lumens

Wattage	Luminaire Lumens (lm)	Nominal Dimensions (mm)
14	1313	600x300
27	2458	600x300
26	2914	600x600
48	5004	600x600
26	2628	1200x300
48	4443	1200x300

SPECIFICATIONS

Dimensions (mm)	
	Actual / Nominal
Length	1190 / 1200
Width	295 / 300
Depth	66
Plaster board cut out sizes (mm)	
Cutout	596x311 / 600x300 1196x311 / 1200x300 605x605 / 600x600

PRODUCT CODE

Example code: REVO-TB/14/6x3/30/ND

See Technical Information Table for configurations options.
Specifications subject to change without notice.

Product Series		Wattage and Nominal Dimensions		Diffuser		LED Type		ECG	
REVO-TB	T-Bar	14/6x3	14W, 600x300mm		White Acrylic (standard)	30	3000K	ND	Non Dimming
REVO-PB	Plaster	27/6x3	27W, 600x300mm	MP	Microprism	40	4000K	DALI	DALI Dimming
REVO-AH	Air Handling	26/6x6	26W, 600x600mm					SD	Switch Dimming
REVO-SM	Surface Mounted	48/6x6	48W, 600x600mm						
		26/12x3	26W, 1200x300mm						
		48/12x3	48W, 1200x300mm						

FREND
lighting

phone 1300 241 087

fax (617) 3272 9000

email sales@foslighting.com.au

PO Box 268

14 Jaybel Street, Salisbury

Brisbane QLD 4107

www.frend.com.au