

ETW

LED WEATHERPROOF



FEATURES


- L70 B50.
- Rated 50,000 hours.
- CRI≥80.
- High efficiency SMD LED chips.
- 5 year warranty (subject to terms and conditions, battery 1 year).
- IP65 weatherproof luminaire.
- IK08 vandal proof.
- High impact polycarbonate body.
- Stainless steel clips and screws.
- High impact polycarbonate diffuser.
- Suitable for suspension (suspension kit is required).

TECHNICAL INFORMATION

Configurations	Lumens	Type	Nominal Dimensions (mm)
20W	2000	Standard	600
40W	4000	Standard, Emergency	1200

SPECIFICATIONS

Dimensions (mm)	
	Actual / Nominal
Length	662 / 600
Width	130
Depth	90



PRODUCT CODE

Example code: ETW/40/12/40/ND

See Technical Information Table for configurations options.
Specifications subject to change without notice.

Product Series		Wattage and Nominal Dimensions	LED Type	ECG
ETW	Surface	20/06 20W, 600mm	40 4000K	ND Non Dim
ETW-SUS	Suspended	40/12 40W, 1200mm	50 5000K	ME Emergency*

*Emergency version only available for 40W.

FREND
lighting

phone 1300 241 087

fax (617) 3272 9000

email sales@foslighting.com.au

PO Box 268

14 Jaybel Street, Salisbury

Brisbane QLD 4107

www.frend.com.au